



A-LINK®

A-LINK SD080A 8 PORT 10/100Mb SWITCH

A-LINK SD080A, 8-port 10/100Mb Switch with MDI-X autosensing ports.

Product specification :

• Standards :

IEEE 802.3 10BASE-T
IEEE 802.3u 100BASE-TX
IEEE 802.3x

• Autosense :

Auto-MDI/MDIX detects and
corrects cabling errors.

• Filtering rate :

14,880 packets per second for 10Mbps port
148,800 packets per second for 100Mbps port

• Forwarding rate :

14,880 packets per second for 10Mbps port
148,800 packets per second for 100Mbps port

• Topology :

- Star

• MAC address :

- 8192

• Buffer memory :

- 256KB

• Forwarding mode :

- Store-and-forward

• Interface :

- 8 x 10/100 Mbps RJ-45 ports

• Transmission mode :

- Half or full duplex

• Protocol :

- CSMA/CD

• Uplink :

- Shared with 8th port

• Flow control :

- Back pressure, IEEE 802.3x

• Panel indicators :

- Per unit: power
- Per port: link/activity/collision,
- 10/100M indication, half/full duplex

• Output of power adapter :

9V DC, 0.5A

• Compliance :

CE, FCC, RoHS

• A-LINK Retail package contains :

- Switch
- Power adapter
- Installation guides

• Product packing:

- Export carton size 20pcs

• Ean / Order code :

6418949 026090

A-LINK is a registered trademark of A-Link.

<http://www.a-link.com>

All rights reserved

SD080A specs UK 12.11.08